

## F/X Camera Interfaces

Three F/X camera interfaces are provided to allow wireless control of camera functions.

The **Arricam Interface** works in conjunction with either the ST or LT models. It provides full control of camera speed and shutter in a minimal sized package.



p/n: 4541  
Size: 1.85 x 2.35 x 1.35 inches ( 47 x 60 x 29mm)  
Weight 4.5 oz (125g)  
Power: Camera Accessory Port  
Cables: 12" (30mm) to Arricam "CAC" receptacle  
10" (25mm) to MDR2 "Camera" receptacle

The **Moviemcam Compact Interface** attaches to the 64-pin accessory port of the camera body.



p/n: 4531  
Size: 108mm x 64mm x 32mm (4.25" x 2.5" x .92")  
excluding hook.  
Weight: 216g (8 oz)  
Power: Camera Accessory Port  
Cable Included: MDR2 to Interface p/n 4536

The **Moviemcam SL Interface** attaches to the accessory port of the camera with a 5mm bolt. It extends only 1.4" (37mm) from the camera and weighs 5.5 oz (150g) including cables.



p/n: 4519  
Size: 1.1 x 1.6 x 1.4 inches ( 28 x 41 x 36mm)  
Weight: 5.5oz (150g)  
Power: Camera Accessory Port.  
Cables: Camera Run (to Fischer 3-pin)  
Interface to MDR-2 Camera Receptacle.