

Micro Force V+F2

The Micro Force V+F2 ("MF2") incorporates the same force sensor technology, which has made the Micro Force an industry standard. Its new output amplifier will drive motors from M26T Heden motors to the full range of Panavision zoom motors.

A new ergonomic design provides a rounded grip for comfortable all-day use. The integral camera run switches allows remote run/stop operation. The MF2 may also be used to provide the zoom function in conjunction with the FI+Z system as well as interface to professional Canon and Fujinon video lenses (having the 12 pin Hirose connector).

The MF2 unit operates over an input voltage range from 12 to 28 volts (30V max.). A series of molded "Y" cables is used to interface with the zoom motor and the accessory connectors on most motion picture cameras.

Specifications:

Size:	6.8x2.6x1.1" (170 x 70 x 28) mm
Weight:	11 oz (.31 kg)
Power Requirements:	12 - 28 VDC
Maximum Motor Current:	1.5A
Motor Direction:	Set by panel switch.

Order Information

- 1100** MF2 Control only
- 1143** Heden Zoom Motor M26T
- 1120** Y cable for 12V Arri cameras
- 1121** Y cable for 24V Arri and Moviecam cameras (3 pin Fischer)
- 1122** Y cable for Panavision cameras
- 1123** Y cable for Aaton (6-pin Lemo)
- 1138** Canon 20-pin Hirose Cable
- 1141** Canon Video 12-pin Hirose
- 1140** Y cable for Sony HD/ Panasonic HD
- 1141** Canon 12-pin Hirose Video Cable
- 1158** Fujinon 12-pin Hirose Video Cable
- 1155** Articulating Pan Arm Adapter

